

# HBO 350W/60V 10/CS 1/SKU



# Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Designed for long lasting performance
- Qualified with major microlithography equipment manufacturers
- Qualified with major microlithography equipment manufacturers

# Areas of application

Microlithography

# Product datasheet

## Technical data

# **General Product Information**

Product number (Americas)	69226		
Product name (Americas)	HBO 350W/60V 10/CS 1/SKU		
Family brand	НВО		
Lamp type	DOUBLE ENDED		
Product remark	Lamp suitable for pulse operation between 250500 W. Maximum permissible power is 350 W for constant power operation. Duty cycle 12 h ON/30 min OFF		
Global order reference	HBO 350 W		


# **Electrical Data**

Nominal wattage	350 W
Nominal voltage	67.5 V
Nominal current	5.3 A
Type of current	DC

## **Photometric Data**

Light center length (LCL)	45.0 mm

# **Physical Attributes & Dimensions**



Electrode gap (cold)	3.0 mm
Base (anode)	SFcY10-4 <sup>1)</sup>
Base (cathode)	SFcY10-4 <sup>1)</sup>
Diameter (in)	0.787 in
Diameter	20.0 mm
Length	128.0 mm
Product weight	106.00 g

 $<sup>^{1)}</sup>$  With 8-32 UNC-3 B thread

#### Product datasheet

# **Operating Conditions**

Burning position	Other <sup>1)</sup>

<sup>1)</sup> Anode underneath

#### Lifetime Data

	Nominal lifetime	400 hr
--	------------------	--------

# **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier	4050300351599		
Declaration no. in SCIP database	69139dd2-ff81-43c7-bcfa-b84bcd0b9cc1		
Candidate list substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		

## Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69226	4050300351599	SHIPPING BOX	1	8.5 in x 2.8 in x 3.7 in	0.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.